

SPECIFICATION FOR DRIZIT® OIL ANTISTATIC SPILL KIT 240



	0170/AS/SK240
Container Size	58 x 74 x 110 cm
Container Volume	240 litres
Container Colour	Yellow
Pack Wt (gross)	58.8 kg
Sorbency	253 - 301 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Container: Heavy duty, UV stabilised highly visible, waterproof, earthed container with two wheels. Fully opening lid allows for ease of access to contents.

Contents:

120	Oil Antistatic Pads
10	Oil Cushions
10	Oil Socks 125 x 7.5 cm
10	Disposal bags and ties

Replenishment: A full refill kit is available for this product. Please use code 0170/AS/SK240/R. To order further kits, refill sets or packs of individual items please contact us.

Instructions for use: It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn. Depending on the nature of the spill a combination of the contents of the kit may be used.

Compatibility: The absorbents within this kit may be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils. Water-repellency exceeds requirements of BS 7959-2:2000. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018