

SPECIFICATION FOR DRIZIT® OIL ONLY BOOMS



	0105/3	0105/4
Size	12.5cm dia x 3m	12.5cm dia x 4m
Colour	Blue	Blue
Pack Quantity	4	4
Pack Wt (gross)	12.6 kg	16.7 kg
Pack Size	70 x 55 x 40 cm	95 x 74 x 34 cm
Sorbency (pack)	120 - 130 litres	160 - 179 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Outer Casing:** 100% polypropylene spun-bonded
Tensile strength (mean): 400N (200mm strip/EN ISO 10319)
High UV resistance
- Filler:** Polypropylene or other fibres
- Fitted with:** 6mm UV stabilized polypropylene rope along length, with 100cm tails for fixing
Polypropylene webbing tapes for positive close joint
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018