

SPECIFICATION FOR DRIZIT® OIL ONLY SOCKS (WHITE)

	0130/125/10/W	0130/125/20/W	0130/125/40/W
Size	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 1.25m
Colour	White	White	White
Pack Quantity	10	20	40
Pack Wt (gross)	3.0 kg	6.1 kg	12.1 kg
Pack Size	40 x 53 x 24 cm	50 x 45 x 40 cm	65 x 45 x 80 cm
Sorbency (pack)	35 - 40 litres	70 - 80 litres	140 - 160 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Outer Casing:	100% polypropylene spun-bonded Tensile strength (mean): 400N (200mm strip/EN ISO 10319) UV resistant
Filler:	Polypropylene and other fibres
Fitted With:	Polypropylene thread tails for joining
Pack Type:	Bag
Compatibility:	Water-repellency exceeds requirements of BS 7959-2:2000.
	May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
	Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
Fire Resistance:	Good. (Physically flame-retardant)
	Incinerable to zero ash.
Disposal:	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
Safety Data:	Refer to our Safety Data Sheet.
	This product is non-toxic to users and to aquatic life.
	Further technical advice is available if required.
Note:	All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018



LEADING PROVIDER OF PRACTICAL POLLUTION CONTROL PRODUCTS AND SERVICES

