

SPECIFICATION FOR DRIZIT® OIL ONLY SWEEPS

	0150/15	0150/30
Size	93cm x 15m x 3mm thick	93cm x 30m x 3mm thick
Colour	Blue	Blue
Pack Quantity	2	1
Pack Wt (gross)	6.6 kg	6.6 kg
Pack Size	100 x 60 x 20 cm	100 x 60 x 20 cm
Sorbency (pack)	85 - 110 litres	85 – 110 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Composition:	>99.5% Polypropylene, <0.5% dye. Meltblown
Basis Wt:	175gsm
Strength:	Mean tensile typically 22N/3cm.
Fitted with:	6mm rope along edge with 2m tails for fixing/towing.
Pack Type:	Bag
Compatibility:	Water-repellency exceeds requirements of BS 7959-2:2000. May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
Fire Resistance:	Good. (Physically flame-retardant) Incinerable to zero ash.
Disposal:	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
Safety Data:	Refer to our Safety Data Sheet. This product is non-toxic to users and to aquatic life. Further technical advice is available if required.
Note:	All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018



LEADING PROVIDER OF PRACTICAL POLLUTION CONTROL PRODUCTS AND SERVICES

