

SPECIFICATION FOR DRIZIT® ULTRA OIL ONLY SPLIT ROLLS



	SRW39DL001BX
Size	33cm x 15m
Perforations	Across every 33cm Along at 10cm and 23cm
Colour	White
Pack Quantity	1
Pack Wt (gross)	2.0 kg
Pack Size	48 x 15 x 49 cm
Sorbency (pack)	29 - 38 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Composition:** 100% Polypropylene
Meltblown, ultrasonically bonded, spunbond laminated on two sides
- Basis Wt:** 17gsm spunbond, 360gsm meltblown, 17gsm spunbond
- Pack Type:** Box
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018